



JP11228748

Biblio

Page 1

**FLAME-RETARDANT POLYOLEFIN RESIN COMPOSITION**

Patent Number: JP11228748
Publication date: 1999-08-24
Inventor(s): OKADA KAZUHIRO
Applicant(s): SEKISUI CHEM CO LTD
Requested Patent: ☐ JP11228748
Application Number: JP19980030160 19980212
Priority Number(s):
IPC Classification: C08L23/00; C08K9/04; C08K13/06
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To obtain a nonhalogen composition having excellent flame retardancy and elongation at break by incorporating a specified amount of a polyolefin resin and a specified amount of an organically treated swelling clay mineral.

SOLUTION: This composition comprises 100 pts.wt. polyolefin resin (e.g. PE) and 1-200 pts.wt. organically treated swelling clay mineral, desirably, smectite, more desirably, montmorillonite and/or hectorite or comprises 100 pts.wt. polyolefin resin, 0.5-100 pts.wt. organically treated swelling clay mineral, and 0.5-100 pts.wt. phosphorus compound being at least one member selected among red phosphorus, polyammonium phosphate, and a phosphorus compound of the formula (wherein R<1> and R<3> are each H, a 1-16C alkyl, or an aryl; and R<2> is R<1>, OH, an alkoxy, or an aryloxy). Alternatively, it comprises 100 pts.wt. polyolefin resin, 1-200 pts.wt. organically treated swelling clay mineral, and 0.01-20 wt.%, based on the clay mineral, metal oxide.

Data supplied from the esp@cenet database - I2